
B

Welding Adaptor
SAS





Ordering Codes

***SAS*-M10x1*-W2**


* Type	Welding Adaptor	**SAS**
* Port Connection	acc. to dimension table	**-M10x1**
* Material Code	Steel, untreated	**-W1**
	Steel, phosphated	**-W2**
	Stainless Steel V2A - 1.4305 (AISI 303)	**-W4**
	Stainless Steel V4A - 1.4571 (AISI 316 Ti)	**-W5**

Thread T	Port Connection	Dimensions (mm/in) h	Ød	Weight (kg/lbs) ca. per 100	Ordering Codes (Standard Option)
M10 x 1	Type A (p. 74)	25	20	4,60	SAS-M10x1-W2
		.98	.79	10.14	
G1/8	Type B/C (p. 75)	25	20	4,70	SAS-G1/8-W2
		.98	.79	10.36	
G1/4		30	22	6,40	SAS-G1/4-W2
		1.18	.87	14.11	
G3/8		30	25	6,90	SAS-G3/8-W2
		1.18	.98	21.16	
1/4 NPT	Type D (p. 76)	25	20	3,80	SAS-1/4NPT-W2
		.98	.79	8.38	
1/2–20 UNF	Type E (p. 77)	25	20	14,00	SAS-1/2UNF-W2
		.98	.79	30.86	

Alternative materials and surface finishings are available upon request. Contact STAUFF for further information.

Adjustable Gauge Fitting
EMV





Ordering Codes

***EMV*-G1/4/G1/2*-B*-OR*-B*-C*-W3**

* Type	Adjustable Gauge Fitting	**EMV**
* Port Connection	acc. to dimension table	**-G1/4/G1/2**
* Seal Material	NBR (Buna-N®)	**-B**
	FKM (Viton®)	**-V**
	EPDM	**-E**
* Seal Type (Female)	with O-ring	**-OR**
* Seal Material	NBR (Buna-N®)	**-B**
* Seal Type	Elastomeric Sealing Type C	**-C**
* Material Code	Steel, zinc/nickel-plated	**-W3**
	Stainless Steel V2A - 1.4305 (AISI 303)	**-W4**
	Stainless Steel V4A - 1.4571 (AISI 316 Ti)	**-W5**

Dimensions (mm/in) T1	T2	h	Hex	Weight (kg/lbs) ca. per 100	Ordering Codes (Standard Option)
G1/4	G1/4	42	19	6,20	EMV-G1/4-B-OR-B-C-W3
		1.65	.75	13.64	
G1/4	G1/2	47	19	11,10	EMV-G1/4/G1/2-B-OR-B-C-W3
		1.85	.75	24.42	
G1/2	G1/4	51	27	13,00	EMV-G1/2/G1/4-B-OR-B-C-W3
		2.01	1.06	28.60	
G1/2	G1/2	55,5	27	18,00	EMV-G1/2-B-OR-B-C-W3
		2.19	1.06	39.60	

Alternative materials and surface finishings are available upon request. Contact STAUFF for further information.

Dimensional drawings: All dimensions in mm (in).